

LENSITIL TOP

Product definition and application

For cleaning transport equipment in shipping and aquaculture, such as well boats, farming floats, for passenger transport and such.

Product type

Lenstitil Top is a cleanser suitable for all types of vessels. It is developed for Norwegian conditions and is effective against fats and fish remains, scraps and soot, as well as oil and diesel spills. The product is gentle against paint, and does not mat down rubber and plastic parts. Aluminum and galvanized surfaces are not affected at the recommended concentration and duration. The product is suitable for manual hand washing, low pressure applications and automatic washing systems.

User instructions

Dosage: 3-5% depending on the nature of the task, the amount of soil and cleaning method (manually, low pressure system, automatic washing plants). If the product is mixed with seawater, it is recommended to increase the dose to 5%.

1. Remove all visible soil.
2. Apply cleanser and leave on for 10 - 15 minutes. The product must not dry on the surfaces.
3. Rinse well with clean water.
4. Lilleborg recommends the use of Addi Aqua for subsequent disinfection. See user information for more information.

Low pressure washing plants are recommended to avoid aerosols that can cross-contaminate cleaned equipment. Cleaning should be performed systematically. Wash the equipment first and finish off with tires, superstructures and railings. Own washing instructions / program for automatic washing well.

Product properties

Foaming ability:	High foaming
Solubility:	Completely soluble at any ratio
Density:	ca. 1,06 kg/l
pH:	ca. 13 (conc.), ca. 11-12 (1-5 % solution)

Storing conditions and durability

Should be used within 5 years of production. Stored frost-free

